

# PHY2054 General Physics II

Section 590986

Prof. Douglas H. Laurence

Exam 2 (Chapters 21 – 23)

July 12, 2018

Name: SOLUTIONS

**Instructions:**

This exam is composed of **10 multiple choice questions** and **4 free-response problems**. To receive a perfect score (100) on this exam, 3 of the 4 free-response problems must be completed. The fourth free-response problem **may** be answered for extra credit, giving a total possible score of 125/100 on the exam. Each multiple choice question is worth 2.5 points, for a total of 25 points, and each free-response problem is worth 25 points, for a total of 75 points. This means that your exam will be scored out of 100 total points, which will be presented in the rubric below. **Please do not write in the rubric below; it is for grading purposes only.**

**Only scientific calculators are allowed – do not use any graphing or programmable calculators.**


For multiple choice questions, no work must be shown to justify your answer and no partial credit will be given for any work. However, for the free response questions, **work must be shown to justify your answers**. The clearer the logic and presentation of your work, the easier it will be for the instructor to follow your logic and assign partial credit accordingly.

The exam begins on the next page. **The formula sheet is attached to the end of the exam.**

**Exam Grade:**

Multiple Choice	
Problem 1	
Problem 2	
Problem 3	
Problem 4	
<b>Total</b>	

MULTIPLE CHOICE QUESTIONS




1. Above,  $A$  and  $B$  are switches: If a switch is closed, current can run through the wire, but if a switch is open, current cannot. In which configuration will the total power emitted by all lightbulbs be greatest?
- (a) Both  $A$  and  $B$  open  
 (b)  $A$  open but  $B$  closed  
 (c) Both  $A$  and  $B$  closed  
 (d) All configurations will emit the same total power

TOTAL POWER IS ALWAYS EQUAL TO POWER OUTPUT OF BATTERY.

2. Consider a cylindrical resistor of radius  $r$ , a length  $L$ , and a resistance  $R$ . If you doubled the radius and doubled the length, what would the new resistance be?

(a)  $R/8$   
 (b)  $R/4$   
 (c)  $R/2$   
 (d)  $2R$

$R = \rho \frac{L}{A} = \rho \frac{L}{\pi r^2}$   
 $R' = \rho \frac{(2L)}{\pi (2r)^2} = \rho \frac{2L}{\pi \cdot 4r^2} = \frac{1}{2} \left( \rho \frac{L}{\pi r^2} \right) = \frac{R}{2}$




3. What is the unknown current  $i$  in the figure above?

- (a) 0.5A  
 (b) 1.5A  
 (c) 2.5A  
 (d) 3.5A

$\sum i_{in} = 2A + 1A = 3A$   
 $\sum i_{out} = 0.5A + i$   
 $3A = 0.5A + i \Rightarrow i = 2.5A$

4. An electron moves to the right in a magnetic field into the page. What direction is the magnetic force on this electron?




- (a) Up  
 (b) Into the page  
 (c) Down  
 (d) Out of the page



RHR SAYS UP, BUT AN ELECTRON IS NEGATIVE, SO THE FORCE IS DOWN.

5. A proton initially moves to the right in the presence of a uniform magnetic field out of the page. Which option correctly describes the motion of the proton?

- (a) To the right, at a constant speed
- (b) To the right, at an increasing speed
- (c) Clockwise in a circle, at a constant speed
- (d) Counterclockwise in a circle, at a constant speed



6. A very long wire, as shown in the figure above, produces a magnetic field at the point indicated. If  $i = 500\text{A}$ , what is the magnitude and direction of this magnetic field?




- (a) 0.0025T into the page
- (b) 0.0025T out of the page
- (c) 0.0033T into the page
- (d) 0.0033T out of the page

$$B = \frac{\mu_0 i}{2\pi r} = \frac{(4\pi \times 10^{-7})(500)}{2\pi(0.03)}$$

$$\Rightarrow B = 0.0033\text{T}$$


7. Two parallel wires carrying currents in opposite directions will produce a force on each other that is:

- (a) Attractive
- (b) Repulsive
- (c) Neither attractive nor repulsive
- (d) No force will be produced in this situation




8. A conductor moves out of the page in a horizontal magnetic field, as shown above. Which point on the conductor is at the lowest potential?

- (a) A
- (b) B
- (c) C
- (d) All are at equal potential



9. In the above figure, the wire carries a current that is decreasing. In what direction through the resistor will the induced current move?


- (a) Up
- (b) Down
- (c) Out of the page
- (d) Into the page



10. A loop moves to the right, passing through a region of uniform magnetic field into the page, as shown above. During which motions will there be an induced current in the loop?

- (a) 1-to-2 and 2-to-3
- (b) 1-to-2, 2-to-3, and 3-to-4
- (c) 1-to-2 and 4-to-5
- (d) 1-to-2, 2-to-3, and 4-to-5

FREE-RESPONSE PROBLEMS



1. In the circuit above,  $R_1 = 1\Omega$ ,  $R_2 = 3\Omega$ ,  $R_3 = 2\Omega$ ,  $R_4 = 1\Omega$ ,  ~~$R_5 = 3\Omega$~~ ,  $R_6 = 2\Omega$ , and the battery is 5V.

- (a) What is the equivalent resistance of this circuit?
- (b) What is the current through  $R_3$ ?
- (c) How much power is produced by  $R_4$ ?
- (d) What is the voltage across  $R_1$ ?


(a)

$R_{46} = R_4 + R_6 = 1 + 2 = 3\Omega$

$$\frac{1}{R_{eq}} = \frac{1}{R_{12}} + \frac{1}{R_3} + \frac{1}{R_{46}} = \frac{1}{4} + \frac{1}{2} + \frac{1}{3}$$
  

$$= \frac{3}{12} + \frac{6}{12} + \frac{4}{12} = \frac{13}{12}$$
  

$$\Rightarrow R_{eq} = \frac{12}{13} \Rightarrow R_{eq} = 0.9\Omega$$




$R_{12} = R_1 + R_2 = 1 + 3 = 4\Omega$

(b)  $R_3$  ALREADY in PARALLEL w/ BATTERY (SEE FIGURE ABOVE), so THE VOLTAGE  $V_3$  EQUALS THE VOLTAGE OF THE BATTERY, 5V.

So,

$$i_3 = \frac{V_3}{R_3} = \frac{5}{2} \Rightarrow i_3 = 2.5A$$

(c) To Get to  $R_4$ , WORK BACKWARDS:



VOLTAGE ACROSS  $R_{46}$  SAME AS ACROSS  $R_{eq}$ , so  $V_{46} = 5V$ .

TO SOLVE FOR ANYTHING TO DO WITH  $R_4$ , WE NEED TO KNOW THE CURRENT THROUGH  $R_{46}$ :

$$i_{46} = \frac{V_{46}}{R_{46}} = \frac{5}{3} = 1.67A$$

THIS IS THE SAME AS THE CURRENT THROUGH  $R_4$  (AND  $R_6$ ),  $i_4 = 0.71A$ .

KNOWING  $i_4$ , WE CAN FIND POWER OUTPUT BY  $R_4$ :


$$P_4 = i_4^2 R_4 = (1.67)^2 (1) \Rightarrow P_4 = 2.8W$$

(d) WORKING BACK AS IN PART (c), WE KNOW  $V_{12} = V_{eq}$ . TO BREAK  $R_{12}$  INTO  $R_1$  &  $R_2$ , WE NEED TO CARRY THE CURRENT. SO:

$$i_{12} = \frac{V_{12}}{R_{12}} = \frac{5}{4} = 1.25A$$

SO,  $i_1 = i_{12} = 1.25A$ , AND THE VOLTAGE ACROSS  $R_1$  IS:

$$V_1 = i_1 R_1 = (1.25)(1) \Rightarrow V_1 = 1.25V$$




2. As shown above, a very long wire carrying a current  $i_1 = 2000\text{A}$  out of the page is placed a distance  $d = 7\text{cm}$  away from a second very long wire, carrying a current  $i_2 = 2500\text{A}$  out of the page.


- What is the magnitude of the force per unit length between each wire? Is it attractive or repulsive?
- What is the magnetic field produced at the center of these two wires? Give both magnitude and direction.
- What would the force on a  $1\text{m}$  wire, carrying a current  $i_3 = 1000\text{A}$  into the page, be if it were placed halfway between the two wires in the above figure? Give both magnitude and direction.

(a) CONSIDER  $i_1$  TO BE PRODUCER &  $i_2$  TO BE FEELER.


AT LOCATION OF  $i_2$



PLACING  $i_2$  IN PRESENCE OF  $\vec{B}_1$ , IT FEELS A FORCE:



(b)



$$B_1 = \frac{\mu_0 i_1}{2\pi r_1} = \frac{(4\pi \times 10^{-7})(2000)}{2\pi (0.035)} = 0.011\text{ T}$$

$$B_2 = \frac{\mu_0 i_2}{2\pi r_2} = \frac{(4\pi \times 10^{-7})(2500)}{2\pi (0.035)} = 0.014\text{ T}$$

CALL DOWN +, AND UP -, THEN:


$$\Sigma B = -B_1 + B_2 = -0.011 + 0.014 = +0.003\text{ T}$$

UP ↑  
DOWN ↓

DOWN ↓

$$\Rightarrow \Sigma B = 0.003\text{ T Down}$$


(c) IF WE PLACE A WIRE, CALL IT  $i_3$ , IN BETWEEN  $i_1$  &  $i_2$ , IT WILL FEEL  $\vec{\Sigma B}$  THAT WE CALCULATED IN PART (b).



$$\vec{\Sigma F}_3 = i_3 l_3 \vec{\Sigma B} = (1000)(0.003)$$


$$\Rightarrow \Sigma F_3 = 3N$$

$\vec{\Sigma F}_3$  IS TO THE **LEFT**



3. Ultimately, what we want to figure out in this problem is the magnetic field at the point  $P$  indicated in the above figure, due to the current  $i$ . However, the shape of this wire – an elongated U – is not a shape we have a ready formula for. We can imagine this as being made up of three different segments of wire: 1) an infinitely long wire at the top, carrying the current to the right; 2) a half-loop of wire, carrying the current clockwise; and 3) an infinitely long wire at the bottom, carrying the current to the left. For this problem, the current is  $i = 200\text{A}$  and the radius of the loop is  $R = 17\text{cm}$ .

- (a) What will the magnitude of the magnetic field produced by these infinitely long wires be? *Hint: we know the magnetic field due to an infinitely long wire with the point halfway down the length of the wire. What would the magnetic field be if we placed this point at the end of an infinitely long wire? Reference the figure below.*



- (b) What will the magnitude of the magnetic field produced by the half-loop be? *Hint: we know the magnetic field produced by a full,  $360^\circ$  loop. What would the magnetic field be if only half that loop,  $180^\circ$ , contributed?*
- (c) What is the direction of the magnetic field produced by each segment?
- (d) Using the answers to parts (a), (b), and (c), find the vector sum of the magnetic field due to each of the three segments of wire at point  $P$ .


(a)  $\infty \leftarrow \text{---} \rightarrow \infty$  we know  $B = \frac{\mu_0 i}{2\pi r}$  FOR THIS WIRE.

$i = 200\text{A}$   
 $r = 17\text{cm} \left\{ \begin{array}{l} \vdots \\ \vdots \end{array} \right. \\ = 0.17\text{m} \cdot P$   
 THIS WIRE IS EXACTLY HALF THE ABOVE,  $\Rightarrow$   
 $B = \frac{\mu_0 i}{4\pi r} = \frac{(4\pi \times 10^{-7})(200)}{4\pi(0.17)}$   
 $\Rightarrow$  EACH WIRE PRODUCES  $B = 0.00012\text{T}$

(b)   
 WE KNOW THIS FULL LOOP WILL PRODUCE  $B = \frac{\mu_0 i}{2R}$  AT ITS CENTER.  
 THIS IS EXACTLY HALF THE LOOP ABOVE,  $\Rightarrow$  WILL PRODUCE:

$$B = \frac{\mu_0 i}{4R} = \frac{(4\pi \times 10^{-7})(200)}{4(0.17)} \Rightarrow B = 0.00037 \text{ T}$$


(c) ALL 3 SEGMENTS PRODUCE MAGNETIC FIELDS INTO THE PAGE.



ALL 3 SEGMENTS INTO PAGE, SO:

$$\Sigma B = B_1 + B_2 + B_3 = 0.00012 + 0.00037 + 0.00012$$

$$\Rightarrow \Sigma B = 0.00061 \text{ T INTO THE PAGE}$$




4. As shown above, a loop is placed in a magnetic field pointing out of the page. The loop has dimensions  $10\text{cm} \times 15\text{cm}$ .

- When the magnetic field is  $B = 1.5\text{T}$ , what is the magnetic flux through the loop?
- If this magnetic field decreased at  $0.2\text{ T/s}$ , what would the induced EMF on the loop be?
- If the resistor shown in the loop was  $8\Omega$ , what would the induced current in the loop be?
- In what direction through the resistor would the induced current flow?

(a)  $\Phi_B = BA = (1.5)(0.1 \times 0.15) \Rightarrow \Phi_B = 0.0025\text{ Wb}$   
 $10\text{cm} \times 15\text{cm}$  or  $\text{Tm}^2$

(b)  $\mathcal{E}_{\text{ind}} = \frac{\Delta\Phi_B}{\Delta t} = \frac{\Delta(BA)}{\Delta t} = A \frac{\Delta B}{\Delta t} = (0.1 \times 0.15)(0.2)$   
 $B$  DECREASES AT  $0.2\text{ T/s}$   
 $\Rightarrow \mathcal{E}_{\text{ind}} = 0.003\text{ V}$

(c)  $i_{\text{ind}} = \frac{\mathcal{E}_{\text{ind}}}{R} = \frac{0.003}{8} \Rightarrow i_{\text{ind}} = 0.00038\text{ A}$



IF  $B_{\text{ext}}$  IS DECREASING, THEN  $B_{\text{ind}}$  MUST POINT IN SAME DIRECTION TO COMBAT THE DECREASE IN  $B_{\text{ext}}$ .

## FORMULA SHEET

- Vectors:

$$\vec{A} \cdot \vec{B} = AB \cos \theta = A_x B_x + A_y B_y + A_z B_z$$

$$|\vec{A} \times \vec{B}| = AB \sin \theta$$

- Physics I Formulae:

$$\sum \vec{F} = m\vec{a}$$

$$W = \vec{F} \cdot \Delta \vec{x}$$

$$W_{tot} = \Delta K$$

$$W_{cons} = -\Delta U$$

$$K = \frac{1}{2}mv^2$$

$$K_i + U_i = K_f + U_f$$

- Electric Forces and Fields:

$$e = 1.6 \times 10^{-19} \text{ C}$$

$$\left. \begin{array}{l} k = 8.99 \times 10^9 \frac{\text{Nm}^2}{\text{C}^2} \\ \epsilon_0 = 8.85 \times 10^{-12} \frac{\text{F}}{\text{m}} \end{array} \right\} k = \frac{1}{4\pi\epsilon_0}$$

$$Q = Ne$$

$$F = k \frac{q_1 q_2}{r^2}$$

$$\vec{F} = q\vec{E}$$

$$E = k \frac{q}{r^2}$$

$$\Phi_E = \vec{E} \cdot \vec{A}$$

$$\Phi_{tot} = \frac{q_{enc}}{\epsilon_0}$$

$$\lambda = \frac{Q}{L} \quad \text{or} \quad \sigma = \frac{Q}{A} \quad \text{or} \quad \rho = \frac{Q}{V} \quad (\text{charge densities})$$

- Electric Potential Energy and Electric Potential:

$$U = k \frac{q_1 q_2}{r}$$

$$\phi = k \frac{q}{r}$$

$$U = q\phi \quad \text{and} \quad \Delta U = q\Delta\phi$$

$$E_{av} = \frac{\Delta\phi}{\Delta x}$$

$$V = \Delta\phi$$

- Capacitance and Dielectrics:

$$Q = CV$$

$$\left. \begin{aligned} C &= \epsilon_0 \frac{A}{d} \\ E &= \frac{\sigma}{\epsilon_0} \end{aligned} \right\} \text{Parallel plate capacitors}$$

- Direct Current Circuits

$$R = \rho \frac{L}{A}$$

$$V_R = iR$$

$$P = Vi = i^2 R = \frac{V^2}{R}$$

$$\sum_{\text{loop}} V = 0 \text{ (Kirchhoff's Loop Rule)}$$

$$\sum i_{\text{in}} = \sum i_{\text{out}} \text{ (Kirchhoff's Junction Rule)}$$

$$R_{\text{eq}} = R_1 + R_2 + R_3 + \dots \text{ (series)}$$

$$\frac{1}{R_{\text{eq}}} = \frac{1}{R_1} + \frac{1}{R_2} + \frac{1}{R_3} + \dots \text{ (parallel)}$$

- Magnetism

$$\mu_0 = 4\pi \times 10^{-7} \frac{\text{Tm}}{\text{A}}$$

$$\vec{B} = \frac{\mu_0}{4\pi} \frac{q\vec{v} \times \vec{r}}{r^3} \text{ (point charge)}$$

$$B = \frac{\mu_0 i}{2\pi r} \text{ (long wire)}$$

$$B = \frac{\mu_0 i}{2R} \text{ (center of a loop)}$$

$$B = \mu_0 \frac{N}{L} i = \mu_0 n i \text{ (center of a solenoid)}$$

$$\vec{F}_B = q\vec{v} \times \vec{B} \text{ (point charge)}$$

$$\vec{F}_B = i\vec{l} \times \vec{B} \text{ (wire)}$$

- Electromagnetic Induction

$$\Phi_B = \vec{B} \cdot \vec{A} = BA \cos \theta$$

$$\mathcal{E}_{\text{ind}} = -\frac{\Delta \Phi_B}{\Delta t}$$